Power Generation Commercial Monitoring at ESB, Ireland.



OSI Pi Conference San Francisco April 2004




Power Generation www.esb.ie

Introductions

- Charlie O'Neill,
 ESB Power Generation,
 Dublin, Ireland
- Malcolm Bates
 Process Informatics Ltd
 Darlington, England




ESB Worldwide



ESB Provide Power Utility Services worldwide





ESB Ireland – Power Generation

- •15 Power Plants
 - •22 Conventional Fossil Units
 - •3 CCGT Units
 - •10 OCGT Units
 - •16 Hydro Units
 - •4 Pumped Storage Hydro Units
- •4750 MW Installed Capacity
- •Peak Market demand 4040 MW
- •Electricity Sales Growth 5-6% pa
- •Over 1.5M Customers
- •Currently 13 PI Servers
 - 200+ Pi users and Growing
 - •PI PrcessBook
 - •PI Datalink
 - •Pi ICE
 - **•OIS PI Applications**
 - •Client Based
 - •Web Intranet Based




In the Beginning......


- Initial Development for OIS Application
 - Technical Performance
 - Plant Availability
 - Staff Commercial Awareness

 Cost of controllable losses identified and displayed in Euro, in near real-time.













Applications Built on Pi Platform

- OIS Hydro
- DAM Monitoring
- OIS Thermal
- OIS Perform
- OIS GPRS
- SCADA Visualisation




















Operating Efficiency Trend									
Power Generation									
Start: 04-Jan-04 End: 10-Apr-04	Generation		Operating Efficiency			Thermal Efficiency		Costs in €,000	
Station-Unit	GWhrs Gen	GWhrs Exp.	Op Eff Gen	Op Eff Exp	2004 Target Operating Eff	Thermal Eff Gen	Thermal Eff Exp	Tot Fuel Cost	Eff Losses
Poolbeg CG14	282	282	99.88	99.88	100.00	31.83	31.83	13,623	17
Poolbeg CG15	269	269	99.42	99.42	100.00	31.79	31.79	13,025	76
Poolbeg SG16	325	311	96.94	96.25	100.00	27.47	26.36	0	0
POOLBEG CCP	876	862	98.55	98.30	98.20	30.05	29.60	26,648	93











Evolution of OIS

- Led by clearly defined Business Requirement
- Operational Performance Metrics to Commercial Performance Control.



- OIS Strategy Underpinned by PI
- One Pillar of ESB Corporate IS Strategy
- Business Critical Applications
- Resilient Technical Architecture
- Supporting Decision Making where and when it counts



Generation Commercial Monitoring

Market Driven Initiative

 Objective – To Minimise Uninstructed Imbalances as an Aid to Commercial Performance Optimisation



What is a UI???

- Each generating station unit is issued with instructions by NCC on the level of production for any given time. This is done via the EDIL system, and is called a *Dispatch Instruction*.
- For the purposes of settlement, the trading day is broken up into 48 half hour periods. So for every half hour period each unit will be expected to produce a specific quantity of electricity.
- Failure of the Unit to comply with an instruction will result in an Uninstructed Imbalance (UI)
- Uls are incurred when a generating unit's metered MWhr output does not match the instructed MWhrs from NCC in any settlement period.
- GCM is a tool to help identify when a unit is generating Uninstructed Imbalances.



Instructed MWs


 Operational Characteristics held in Module Database

Updated Daily via File Transfer

Used to Plot Instruction Profile




- •The instructed profile gives us the MW values to be achieved at particular times
- •The area under this profile gives us the MWh targets (Instructed Quantities) for any time period t.






•The area under the actual generated (MW) gives us the Actual Generation in MWh






•Uninstructed Imbalance is the variance between Generated MWh and Target MWh































GCM Provides Operators:

- Visualisation of the current operational state
- On-screen, real-time verification of their actions
- Predictive output for the trading period
- Visual Alarms on screen
- Optional Alarm into DCS/SCADA system



Challenges Overcome

 Real time B2B Integration across physical and commercial boundaries

Compressed Timescale (Are we there yet....)

 Fluid specification in some areas due to changing Regulatory Environment.



Where do we go from here...

- Increased use of Pi ICE and ProcessBook.
- Development of KPIs in Pi ACE
- Further Reinforcement of Technical Architecture
- Increased Focus on Key Benefits Delivery



Acknowledgements

- MDC Technology Ltd.
- Process Informatics Ltd.
- TQS Integration Ltd.



Questions?

